Computer Organization

Purpose: In-depth understanding of the inner workings of modern computers

Study of the hierarchy of layers that comprise computer systems -

- Hardware
- Systems Software
- Applications Software


Principle of Abstraction

Applies equally to Hardware and Software

Work at level appropriate to task - higher level \Rightarrow less detail, lower level \Rightarrow more detail

What is Computer Architecture?

Coordination of levels of abstraction under a set of rapidly changing forces



Instruction Set Architecture


Key interface between levels of abstraction

Interface between hardware and lowest level software

Interface/functionality separated from implementation

Implementation influences design

Hardware - Simple View



Processor

 ${\bf Datapath\ -\ performs\ arithmetic\ operations}$

Control - controls datapath, memory, I/O

Memory

Main or Primary memory - DRAM

Cache - small, fast buffer for DRAM memory

Network

 ${\bf Communication/Resource\ sharing/Non-local\ access}$

Local area networks - Ethernet, Token ring, FDDI (Fiber Distributed Data Interconnect), ATM (Asynchronous Transfer Mode)

Wide area networks - ISDN (Integrated Services Digital Network), ATM

I/O

Mouse

Keyboard

Graphics display \rightarrow Raster CRT display

- Refresh rate 30 to 60 frames/sec (no flicker)
- \bullet Resolution 512x340 to 1560x1280 pixels
- Hardware support raster refresh buffer for bitmap of image
 - − black & white 1 bit per pixel
 - gray scale 8 bits per pixel
 - color 8 bits for each primary color (red, blue, green)

I/O - Permanent Storage

Secondary memory - non-volatile, magnetic

Magnetic hard disk -

- ullet collection of metal platters
- 3600 to 5400 rpm
- ullet covered with magnetic recording material on both sides
- diameter 10.25-1.3"
- movable arm contains electro-magnetic coil or read-write head
- mechanical 5-20 msec vs 50-150 nsec for DRAM

Secondary storage (continued)

Floppy disk - made of mylar vs. metal - flexible, removable

Magnetic tape - cheaper, slower, sequential - access time in seconds

CD-ROMs - Optical

Technology Trends

...and their influence on design and organization

Capacity doubling about every 1.5 years

Challenge: make use of increased capacity

Important Characteristics

Performance

Price

Physical/functional characteristics

New ideas

Hardware -

- pipelining
- superscalar design
- ullet access locality exploitation (cache)

Software - solve larger, harder problems, e.g. human genome project.

Hardware Cost

$$DieCost = \frac{Wafer\ Cost}{Dies\ per\ Wafer \times Die\ Yield}$$

$$Die\,Yield = Wafer\,Yield \times \{1 + \frac{Defects\,per\,unit \times Die\,area}{a}\}^{-a}$$

Typical values: Wafer Yield = 90%, Defects per unit area = 1 cm^2 , a = 2 or 3

The bigger the chip, the less likely it is to come out working correctly

Summary

All computers consist of five components -

- Processor : datapath and control
- Memory main memory, cache
- Input and Output devices disks, networks

Principle of abstraction helps to deal with complexity and handle each aspect independently

The instruction set architecture is the abstract interface between hardware and low-level software that enables implementations of varying cost and performance to run identical software Assignment: Read

- Chapter 2 of Tanenbaum
- Chapter 1 of Hennessy & Patterson