

Peer-to-Peer Networks


Kai Shen

11/3/2014

CSC 257/457 - Fall 2014

1

Distributed Search I: Napster (central index)




11/3/2014

CSC 257/457 - Fall 2014

2

Distributed Search II: Gnutella (query flooding)




11/3/2014

CSC 257/457 - Fall 2014

3

Distributed Search III: Random walk



11/3/2014

CSC 257/457 - Fall 2014

4

Distributed Search IV: Object-addressable network

- "great-song.mp3" is deterministically hashed into location "L"
- every node forwards each query to a neighbor heuristically closer to "L"

How does routing work?

11/3/2014 CSC 257/457 - Fall 2014 5

Scalable Object-addressable Network

Content-addressable net:

- each node owns a region in a virtual 2-D space
- "great-song.mp3" is hashed into a virtual location "L" (1.3, 2.4)
- every node forwards each query to a neighbor heuristically closer to "L"

11/3/2014 CSC 257/457 - Fall 2014 6

Analysis

Content-addressable network [Ratnasamy et al. 2001]:

- each node owns a region in a virtual 2-D space
- each object is hashed into a virtual location "L"
- every node forwards each query to a neighbor heuristically closer to "L"

Questions:

- Space consumption? Lookup cost for a network of N nodes?
 - 4 links per node; $O(N^{1/2})$
- Can the lookup cost be improved?
- Can we take into account the actual link latency?

11/3/2014 CSC 257/457 - Fall 2014 7

Chord [Stoica et al. 2001]

- Each object is mapped to the first node in the clockwise direction on the ring.
- Every node maintains links to
 - the node half-way in the circular ID space
 - the node a quarter-way across the circular ID space
 - ...
- Space consumption? Lookup cost for a network of N nodes?

11/3/2014 CSC 257/457 - Fall 2014 8

Distributed Hashtables

- Content-addressable network (CAN) [Ratnasamy et al. 2001] and Chord [Stoica et al. 2001] are also called scalable distributed hash tables (DHTs)
- There are other scalable DHT protocols.

11/3/2014

CSC 257/457 - Fall 2014

9

Geographic Location-based Routing

- Bunch of wireless sensors (not mobile)
- Each is identified by its geographic location (longitude, latitude)
- Routing – a packet is routed to a neighbor with shortest geographic distance to the destination
- Con
 - May not always find valid path
- Pro
 - Very simple, no maintenance
 - Simple rule to avoid routing loop

11/3/2014

CSC 257/457 - Fall 2014

10

Peer-to-peer Networks

- Peer-to-peer networks: distributed systems of **no hierarchy** – each node is a peer of any other in terms of equal functionality
 - DNS? Napster? Gnutella? Random walk? DHTs (CAN and Chord)? GLR?
- Fundamental advantage of p2p networks
 - better scalability?
 - no performance bottleneck
 - better robustness?
 - no single point of failures; more tolerant to intentional attacks

11/3/2014

CSC 257/457 - Fall 2014

11

More on Scalability & Robustness

- Scalability:** able to support large number of nodes
 - cost of each operation is below linear-scaling – goes up slowly when the system size increases: $O(n)$ is terrible, $O(n^{1/2})$ is OK, $O(\log n)$ is good.
 - space requirement at each node is below linear-scaling.
 - Gnutella? Random walk? CAN? Chord?
- Robustness:** complexity of repair mechanism is a very important issue
 - Gnutella? Random walk? CAN? Chord?

11/3/2014

CSC 257/457 - Fall 2014

12

Where are we now?

- Several approaches for searching large, distributed systems:
 - central index
 - query flooding
 - random walk
 - hash + heuristics-based routing (DHT)
- Concept of peer-to-peer networks.
- Additional p2p services, built on distributed search
 - p2p DNS
 - p2p file sharing
 - p2p keyword search

11/3/2014

CSC 257/457 - Fall 2014

13

P2P DNS

- DNS running on scalable DHT like Chord or CAN
 - Scalable and robust
 - Accesses aren't always local
- A hybrid approach
 - Retain local DNS server and caching
 - Support search of destination authoritative server using scalable DHT
 - ⇒ no need for root servers

11/3/2014

CSC 257/457 - Fall 2014

14

P2P Sharing of Large Files – BitTorrent

- Downloading large files is slow and unreliable
 - Chop a large file into pieces and try to download each piece
- How to find who has a particular piece of the file?
 - Distributed search: Gnutella, Chord, CAN, ...
- Downloading approach:
 - Rarest-first ⇒ high chance of completion
 - Multiple TCP connections for downloading

11/3/2014

CSC 257/457 - Fall 2014

15

Keyword Search

- User inputs a few keywords, the system returns a list of documents matching the keywords – Google
- Google maintains a central search index:
 - a search index contains a list of all searchable words, each of which contains a list of documents relevant to the word
 - intersection of document lists for multiple-word queries

Java:

Page #123	Page #157
-----------	-----------	-----	-----

Sun:

Page #157	Page #468
-----------	-----------	-----	-----

... ..

11/3/2014

CSC 257/457 - Fall 2014

16

