



Determining Nearby Content Server

- We create a "map", indicating distances between Internet machines (or networks) and content servers
- When a DNS query arrives at authoritative DNS server:
 - server determines network location from which guery originates
 - uses "map" to determine a nearby content server
- How to build the map?
 - offline pings from content servers to all network locations
 - just-in-time pings from content servers to the source
 - What if the source does not respond to pings?

11/10/2014

CSC 257/457 - Fall 2014

5



A Related Question

- Scalable estimation of node-to-node relative proximity
 - A specific problem: given any node X, find a few nearby nodes in a group of 10,000 nodes (N₁, ..., N₁₀₀₀₀).
 - Too costly to measure the distance from X to 10,000 nodes.
- Use a landmark L:
 - Measure the distances from N₁, ..., N₁₀₀₀₀ to L offline.
 - Given node X, we measure the distance from X to L.
 - For node N, if distance(X,L) differs significantly from distance(N,L), X and N are likely far apart.
 - If distance(X,L) is similar to distance(N,L), does it mean X and N are nearby?
- Use multiple landmarks

11/10/2014

CSC 257/457 - Fall 2014



Another Related Question

- How to build a map indicating the geographical location of machines or local networks?
 - User registrations
 - GPS information

11/10/2014

CSC 257/457 - Fall 2014




Web caches (proxy server)


- Cache is installed and shared by users (university, company, residential ISP)
- Goal: satisfy client requests without involving the original server.
- User sets browser: accesses via Web cache
- Browser sends all HTTP requests to Web cache
 - object in cache: cache returns object
 - otherwise cache requests object from the original server, then returns to client


11/10/2014


CSC 257/457 - Fall 2014




2











Mining of Cache Logs

- Web cache logs contain a wealth of information
 - List of who accessed what at when
- Mine to learn useful statistics
 - Most popular web objects, distribution of web object popularity
 - General user access models (think time between accesses, pattern of page browsing sequence, ...)
 - **...**
- User privacy

11/10/2014

CSC 257/457 - Fall 2014


13




Web Prefetching

- Prefetch a web page before client makes access
 - Reduce latency, but not bandwidth
- Prefetching heuristics?
 - Hyperlinks in the current page (assume client may click some of them)
 - Predict future accesses based on past browsing history
- Benefit vs. cost

11/10/2014 CSC 257/457 - Fall 2014





14



Summary

- Several means:
 - By content providers replicated, distributed Internet sites
 - By content consumers (or clients) Web caching, prefetching
 - By a third-party content distribution network
- Differentiate them on the following:
 - Scalability
 - Content staleness
 - Transparency to clients
 - Reliance on the Domain Name System

11/10/2014

CSC 257/457 - Fall 2014

17