

























#### **Mobile IP**

- Network-layer mobility protocol interoperable with IP [C. Perkins, 2002]
- Has many features we've seen:
  - home agents, foreign agents, foreign-agent registration, care-ofaddresses, encapsulation (packet-within-a-packet)
  - use indirect routing

11/19/2014

CSC 257/457 - Fall 2014

13

15



### **Ad Hoc Network Model**

- No base stations or access points
- Wireless hosts communicate with each other directly
  - to get packet from wireless host A to B may need to route through wireless hosts X, Y, Z
- Compared with based station model
  - more flexible
  - require complex support
- Application scenarios:
  - "laptop" meeting in conference room
  - cars on the road
  - interconnection of "personal" devices
  - emergency/battlefield

11/19/2014

CSC 257/457 - Fall 2014 14



# **Addressing in Ad Hoc Networks**

- Requirements for Internet addressing
  - unique
  - hierarchical
- Requirements for addressing in ad hoc networks?

11/19/2014

CSC 257/457 - Fall 2014



# **Routing in Ad Hoc Networks**

- How does ad hoc network routing differ from routing on infrastructured networks?
- DSR [Johnson 1994]
  - No routing table; source maintains whole path, each packet carries whole path
  - Broadcast-style path discovery
- AODV [Perkins and Royer 1999]
  - Every node maintains a routing table; routing hop by hop
  - Broadcast-style path discovery when route to destination is missing; cut short when reaching a node with known routing to destination
  - Routes in routing table may become invalid due to mobility

DSR vs. AODV?

11/19/2014

CSC 257/457 - Fall 2014

16



# **Sensor Networks**

- Wireless ad hoc (but not mobile) networks
  - Without mobility, standard network routing (for Internet) works quite well

11/19/2014

CSC 257/457 - Fall 2014

17

19



# **Geographic Location-based Routing**

- [Li et al. 2000]
  - Each device is identified by its geographic location (e.g., longitude and latitude)
  - At each routing step, the packet is directed to the current node's neighbor with shortest Cartesian distance to dest.
- Advantage:
  - Simple scheme, low routing overhead
- Problem?
  - Routing loops or "dead ends"
  - Work best for dense networks

11/19/2014

CSC 257/457 - Fall 2014

18



# **Disclaimer**

 Parts of the lecture slides contain original work of James Kurose, Larry Peterson, and Keith Ross. The slides are intended for the sole purpose of instruction of computer networks at the University of Rochester. All copyrighted materials belong to their original owner(s).

11/19/2014

CSC 257/457 - Fall 2014