

IMPORTANT: Write each problem on a separate sheet of paper. Write your name on each sheet. (Why? To speed up the grading we will use parallelization—each problem will be graded by a different TA. At the beginning of the class (on the date when the homework is due) there will be a separate pile for each problem.)

1 Homework - solve and turn in

1.1 (due Sep. 15) Write a dynamic programming algorithm which for a given number n finds the smallest number of squares which sum to n (for example for $n = 7$ we need 4 squares ($7 = 2^2 + 1^2 + 1^2 + 1^2$), whereas for $n = 13$ we only need 2 squares ($13 = 3^2 + 2^2$)). Implement your algorithm and find all numbers from $\{1, 2, \dots, 100\}$ which need 4 squares. Use “The On-Line Encyclopedia of Integer Sequences” to find a formula for the numbers which need 4 squares.

1.2 (due Sep. 15) We are given n positive numbers a_1, \dots, a_n . The goal is to select a subset of the numbers with maximal sum and such that no three consecutive numbers are selected. Here are three example inputs together with optimal solutions (the numbers in boxes are selected):

$$\begin{array}{cccccc} \boxed{5} & \boxed{5} & 8 & \boxed{5} & \boxed{5} & \\ & \boxed{5} & 5 & \boxed{12} & 5 & \boxed{5} & \\ 1 & \boxed{2} & \boxed{2} & 1 & \boxed{2} & \boxed{1} & 2 & \boxed{5} & \boxed{5} \end{array}$$

Give an $O(n)$ -time algorithm for the problem.

1.3 (due Sep. 15) We are given an $n \times n$ array A of zeros and ones. We want to find the size of the largest contiguous all-ones square. Give an $O(n^2)$ -time algorithm for the problem.

2 Bonus Homework - solve and turn in

1.4 (due Sep. 15) We have an $a \times b$ bar of chocolate (where a, b are integers). By breaking the bar we can either

- create two bars $a_1 \times b$ and $a_2 \times b$ where a_1, a_2 are integers and $a_1 + a_2 = a$, or
- create two bars $a \times b_1$ and $a \times b_2$ where b_1, b_2 are integers and $b_1 + b_2 = b$.

We can further break the resulting bars. Our goal is to 1) end up with bars that are square (that is, have size 1×1 , or 2×2 , or 3×3 , and so on) and 2) minimize the total number of breaks.

For example, if $a = 2$ and $b = 3$ then we use 2 breaks:

$$\begin{array}{l} 2 \times 3 \rightarrow \\ 2 \times 2 \text{ and } 2 \times 1 \rightarrow \\ 2 \times 2 \text{ and } 1 \times 1 \text{ and } 1 \times 1. \end{array}$$

For example, if $a = 2$ and $b = 4$ then we use 1 break:

$$\begin{array}{l} 2 \times 4 \rightarrow \\ 2 \times 2 \text{ and } 2 \times 2. \end{array}$$

Give a dynamic programming algorithm which computes a table $T[1..a, 1..b]$ where $T[x, y]$ contains the minimal number of breaks to “squareize” an $x \times y$ bar.