

**IMPORTANT: Write each problem on a separate sheet of paper. Write your name on each sheet.** (Why? To speed up the grading we will use parallelization—each problem will be graded by a different TA. At the beginning of the class (on the date when the homework is due) there will be a separate pile for each problem.)

**Homework 5 is due: Dec. 8 (Thursday);** collected before class in B&L 109.

Problem sessions before Homework 5 is due:

Dec. 5 (Monday) 6:15pm - 7:15pm in Hylan 202

Dec. 6 (Tuesday) 6:15pm - 7:15pm in in Goergen 109

Dec. 7 (Wednesday) 6:15pm - 7:15pm in Gavett 310

Dec. 7 (Wednesday) 7:40pm - 8:40pm in Hutchinson 473

**Comprehensive Final Exam** is on Dec. 21 (Saturday) 4:00pm - 7:00pm in B&L 109.

## 1 Homework - solve and turn in

**5.1 (due Dec 8)** We are given a string  $S$  over alphabet  $\Sigma = \{a, b\}$ . We want to find a cyclic rotation of  $S$  that disagrees with the original string  $S$  on the maximal number of places.

For example, if  $S = ababb$  then there are 5 cyclic rotations of  $S$ :  $ababb$  (0),  $babba$  (4),  $abbab$  (2),  $bbaba$  (2),  $babab$  (4); the numbers in the parenthesis give the number of places on which the rotations disagree with  $S$ . Thus the output should be either  $babba$ , or  $babab$ .

Give an  $O(n \log n)$ -time algorithm for the problem.

**5.2 (due Dec 8)** Let  $A$  and  $B$  be two sets. Their sum  $A + B$  is defined to be

$$A + B := \{a + b \mid a \in A, b \in B\},$$

for example if  $A = \{1, 4, 6\}$  and  $B = \{2, 5\}$  then  $A + B = \{3, 6, 8, 9, 11\}$ . Give  $O(n \log n)$  algorithm whose input is two sets  $A, B \subseteq \{1, \dots, n\}$  and the output is set  $A + B$ .

**5.3 (due Dec 8)** The Hadamard matrices  $H_0, H_1, \dots$ , are defined as follows.

- $H_0$  is the  $1 \times 1$  matrix  $[1]$ .
- For  $k > 0$ ,  $H_k$  is the  $2^k \times 2^k$  matrix

$$H_k = \left[ \begin{array}{c|c} H_{k-1} & H_{k-1} \\ \hline H_{k-1} & -H_{k-1} \end{array} \right].$$

Show that if  $v$  is a column vector of length  $n = 2^k$  then the matrix-vector product  $H_k v$  can be calculated using  $O(n \log n)$  operations. (Assume that all the numbers involved are small enough that basic arithmetic operations take  $O(1)$  time.)

**5.4 (due Dec 8)** Consider the following search problem:

INPUT: undirected graph  $G = (V, E)$

OUTPUT: labeling  $\phi$  of the vertices of  $V$  by numbers  $\{1, \dots, |V|\}$  such that

- each vertex receives a different label; and

- for every  $\{u, v\} \in E$  the labels of  $u$  and  $v$  differ by at least 2 (that is,  $|\phi(u) - \phi(v)| \geq 2$ ).

Example #1: for

$$G = (\{a, b, c, d, e\}, \{\{a, b\}, \{b, c\}, \{c, d\}, \{d, e\}, \{e, a\}\})$$

$\phi(a) = 1, \phi(b) = 4, \phi(c) = 2, \phi(d) = 5, \phi(e) = 3$  is a valid labeling.

Example #2: for

$$G = (\{a, b, c, d\}, \{\{a, b\}, \{b, c\}, \{c, d\}, \{d, a\}\})$$

no valid labeling exists.

Give a direct<sup>1</sup> reduction of the problem to Integer Linear Programming. Clearly describe the variables and constraints in your program.

---

<sup>1</sup>your reduction may not use any intermediate problem; also you cannot rely on Cook's theorem.