# CSC2/455 Software Analysis and Improvement Live variable analysis

Sreepathi Pai

January 29, 2024

URCS

Live Variable Analysis

Live Variables using Iterative Data flow Analysis

Live Variable Analysis

Live Variables using Iterative Data flow Analysis

- Basic blocks to Control Flow Graphs
  - Section 5.4.3 in Cooper and Turczon
- Local optimizations (Value Numbering)

Live Variable Analysis

Live Variables using Iterative Data flow Analysis

```
void example(int x) {
    int a = 0;    /* def 1 */
    int b = 0;    /* def 2 */
    if(x > 1) {
        a = b;    /* def 3 */
    } else {
        a = x;    /* def 4 */
    }
    return a;
}
```

Must the compiler emit code to initialize a to 0?

```
void example(int x) {
    int a = 0;    /* def 1 */
    int b = 0;    /* def 2 */
    if(x > 1) {
        a = b;    /* def 3 */
    } else {
        a = x;    /* def 4 */
    }
    return a;
}
```

a is *defined* (i.e. written) thrice in the code above. Which definitions are "alive" at return a?

- A variable x is live at a definition (i.e. a write) if there is a subsequent read of the variable along a program path from that definition.
  - Alternatively: is this variable overwritten along all paths before a subsequent read?
- Can we identify live variables just by analyzing basic blocks (i.e. local analysis)?

```
void test() {
    int i;
    // begin delay
    for(i = 0; i < 10000; i++);
    // end delay
}</pre>
```


## GCC without optimization

<pre>test():</pre>				
	push	rbp		
	mov	rbp, rsp	F	
.L3:	mov	DWORD PTR	[rbp-4],	0
.L3:	6 <b>m</b> 70	DWORD PTR	[rbn=4]	0000
	cmp jg	.L4	Liph-4],	99999
	J& add	DWORD PTR	[rbp-4].	1
	jmp	.L3	L- 0p -1),	-
.L4:	5 1			
	nop			
	рор	rbp		
	ret			

Code courtesy Compiler Explorer at godbolt.org (this is more convenient than gcc -Wa if you have access to the Internet)


test():
 ret

Code courtesy Compiler Explorer at godbolt.org



### Example 2

- Which definition(s) of x are live at entry of loop?
- Which definition(s) of x are live in the loop?
- Which definition(s) of x are live at exit of loop?



```
i = 1;
L1:
    if(!(i < 10000)) goto L2;
    i++;
    goto L1;
L2:
    return
```

Where in the CFG must i be "dead" to eliminate it?


For a basic block s:

- DEF(s) (for "defined") is the set of variables written by s
- USE(s) is the set of variables read by s

For the blocks below, what are the  $\mathrm{DEF}$  and  $\mathrm{USE}$  sets?

```
BB_eg_0:
    i = i + 1
BB_eg_1:
    a = x;
    x = 3;
BB2_eg_2:
    t = a;
```

#### Effects of definitions and reads




- What happens to a definition of a in a basic block that is before BB\_eg\_3 on some path through the CFG?
- What can we say about definitions of y in other basic blocks that are before BB\_eg\_3 on some path through the CFG?


- Upwardly exposed UE(s) are those variables that are read *before* they are written to in basic block s.
  - e.g. x and y in BB\_eg\_3 in the previous slide
- A variable is alive in a basic block if it is in the set:
  - ?
- A variable is killed in a basic block if it is in the set:

• ?

- Start from the definition, and see if it "reaches" a use
  - i.e., it is not killed on some path (in the CFG) to a use
- Start from a use, and walk backwards to see if you can reach the definition
  - Repeat for all uses

Example #1





When does enumerating paths work in practice?

- Setup data flow equations
- Solve these data flow equations

Live Variable Analysis


Live Variables using Iterative Data flow Analysis

## **Equations for Live Variables**



- Each basic block has "incoming" edges (from predecessors) and "outgoing" edges (to successors).
- When is an "incoming" variable live "into" a block?
  - it is in UE for that block
- When is a variable live out of a block n?
  - it is live into a successor block m
  - first try:  $LIVEOUT(n) = \bigcup_m UE(m)$  (where  $m \in succ(n)$ )
  - what are we missing?

## **Complete equation**



 $LIVEOUT(n) = \bigcup_{m \in succ(n)} UE(m) \cup (LIVEOUT(m) \cap \overline{DEF(m)})$ 

The variables live out of block *n* must:

- be upwardly exposed in a successor m
- OR be live out of m and NOT be killed by m (i.e.  $\overline{\text{DEF}(m)}$ )
  - note this is equivalent to (LIVEOUT(m) DEF(m))

How would you begin solving this equation?

- Live variables is a backwards dataflow analysis
  - "Facts" flow from a node's successors to it
- Initialization:
  - Compute DEF(s) for all blocks s
  - Compute UE(s) for all blocks s
  - Set  $LIVEOUT(s) = \emptyset$  for all s
- Repeat (iterate):
  - Compute LIVEOUT(s) for all blocks s
  - Until no set LIVEOUT(s) changes i.e. until a fixpoint is reached.

- Termination
  - Note LIVEOUT(s) only increases in size or remains the same in every iteration
  - What is the maximum size of LIVEOUT(s)?
- Correctness
  - When the algorithm terminates, all computed LIVEOUT(s) sets satisfy the equation
  - and hence meet the definition of "liveness".

How does the iterative solution differ from the path-based solution?

Live Variable Analysis

Live Variables using Iterative Data flow Analysis

- Chapter 8 of Cooper and Turczon
  - Section 8.6.1
- Also recommended:
  - Aho, Lam, Sethi and Ullman, Chapter 9, Section 9.2.5
- Spare time reading (esp. for PhD students):
  - Frances E. Allen, John Cocke, 1971, A Catalogue of Optimizing Transforms